

What is claimed is:

- 1 An optical network comprising:
 - a central source providing light in a plurality of spaced wavelength bands and including variable-gain optical amplifiers enabling the relative intensity of light in
 - 5 respective wavelength bands to be varied;
 - plural distributed terminals operable to modulate and return received light in any of the said wavelength bands; and
 - a wavelength-routed network receiving light in all the said wavelength bands from the central source and routing each wavelength band to a respective one of the terminals.
- 10 2 An optical network as claimed in claim 1 in which the variable-gain optical amplifiers are an array of semiconductor optical amplifiers and are followed by a wavelength-division multiplexer for receiving their outputs and passing them together to the wavelength-routed network.
- 3 An optical network as claimed in claim 2 in which the semiconductor optical
- 15 amplifiers are also preceded by a wavelength-division demultiplexer receiving light from a single multi-band source.
- 4 An optical network as claimed in claim 1 in which the central source is a spectral-slicing source in which light in a continuous range of wavelengths is generated and spaced wavelength bands selected from it.
- 20 5 An optical network as claimed in claim 4 in which the light generator is selected from the group consisting of
 - rare-earth doped fibre amplifiers,
 - semiconductor optical amplifiers,
 - super-continuum sources,
 - 25 • mode-locked lasers
 - superluminescent diodes,
 - other light-emitting diodes of sufficient optical power and spectral bandwidth, and
 - wavelength combs.
- 30 6 An optical network as claimed in claim 5 comprising wavelength-division multiplexers for slicing to obtain the required spaced wavebands, said multiplexers being selected from the group consisting of arrayed-waveguide gratings, thin-film filters,

directional couplers, and filters of the blazed-grating type.

7 An optical network as claimed in claim 1 in which at least some terminals each comprise a reflection modulator.

8 An optical network as claimed in claim 1 in which all the terminals are substantially
5 identical.

9 An optical network as claimed claim 1 in which the said wavelength-routed network is entirely passive.

10 A method of controlling an optical network comprising forming the network with:
a central source providing light in a plurality of spaced wavelength bands and
10 including variable-gain optical amplifiers enabling the relative intensity of light in
respective wavelength bands to be varied;
plural distributed terminals operable to modulate and return received light in any of
the said wavelength bands; and
a wavelength-routed network receiving light in all the said wavelength bands from
15 the central source and routing each wavelength band to a respective one of the
terminals

and adjusting the said variable optical amplifiers individually to determine the level of light reaching the respective terminals.

11 An optical network comprising:

20 a central source providing light in a plurality of spaced wavelength bands, the
relative intensity of light in respective said wavelength bands being individually variable;
plural distributed terminals operable to modulate and return received light in any of
the said wavelength bands; and

a wavelength-routed network receiving light in all the said wavelength bands from
25 the central source and routing each wavelength band to a respective one of the terminals.

12 A method of controlling an optical network comprising forming the network with:
a central source providing light in a plurality of spaced wavelength bands, the
relative intensity of light in respective said wavelength bands being individually
variable;

30 plural distributed terminals operable to modulate and return received light in any of
the said wavelength bands; and

a wavelength-routed network receiving light in all the said wavelength bands from

the central source and routing each wavelength band to a respective one of the terminals

and adjusting the relative intensity of light in respective said wavelength bands individually to determine the level of light reaching the respective terminals.